

NOTICE: Ensuring subscriber access to content on IOPscience throughout the coronavirus outbreak - see our remote access guidelines.

IOP Science home

Journals

Journal of Physics: Conference Series

PAPER • THE FOLLOWING ARTICLE IS OPEN ACCESS

The Strength characteristics of Chitosan- and Titanium- Poly (L-lactic) Acid Based Composites

Abraham Kehinde Aworinde¹, Samson Oluropo Adeosun^{1,2}, Festus Adekunle Oyawale¹, Esther Titilayo Akinlabi^{1,3} and Stephen A. Akinlabi^{1,3}

Published 1 December 2019 • Published under licence by IOP Publishing Ltd

Journal of Physics: Conference Series, Volume 1378, Issue 2

Abstract

The problem of bone fracture and the need to avoid revision surgery in osteosynthesis are the critical reasons for the gradual shift from the use of metallic fixations to the polymeric scaffold in the orthopaedic applications. However, the mechanical properties of polymers that have become a substitute for metals need to be improved upon. An attempt was made to improve the mechanical properties of poly(L-lactic) acid (PLLA), a biopolymer, by loading it with 1.04, 2.08, 4.17, 8.33 and 16.67 wt.% of chitosan (an organic filler) and Ti-6Al-2Sn-2Mo-2Cr-0.25Si (an inorganic particle). Melt blend technique was the processing technique. Hardness, compressive modulus and fracture toughness of virgin PLLA improved significantly while the resulting composites were found to be less ductile than unreinforced PLLA. Titanium reinforced PLLA displayed superior mechanical properties over the neat and chitin reinforced PLLA. Compressive modulus values of the developed composites were much lower than the modulus of cortical bone, they were, however, mechanically compatible with the properties of cancellous bone. Optical microscopy images also show the formation of pores which are a catalyst for cell proliferation and cell differentiation.

Export citation and abstract BibTeX RIS

Content from this work may be used under the terms of the Creative Commons Attribution 3.0 licence. Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI.

REFERENCES

[1]

Gbenebor O. P., Atoba R. A., Akpan E. I., Aworinde A. K., Adeosun S. O. and Olaleye S. A. TMS 2018 147th Annual Meeting & Exhibition Supplemental Proceedings, M. & Materials Society, The Minerals (Ed. Cham: Springer International Publishing, 2018) Study on Polylactide-Coconut Fibre for Biomedical Applications 263-273

Google Scholar

[2]

Li C. et al 2016 Severe pathological fractures caused by vertebral hemangiomas with posterior decompression, bone cement augmentation and internal fixation Orthop. Traumatol. Surg. Res. 102 489-494

CrossrefGoogle Scholar

[3]

Murariu M. and Dubois P. 2016 PLA composites: From production to properties Adv. Drug Deliv. Rev. 107 17-46 Dec.

CrossrefGoogle Scholar

[4]

Deepthi S., Nivedhitha Sundaram M., Deepti Kadavan J. and Jayakumar R. 2016 Layered chitosan-collagen hydrogel/aligned PLLA nanofiber construct for flexor tendon regeneration

Carbohydr. Polym.

CrossrefGoogle Scholar

[5]

Ya'ish F., Bailey C. A., Kelly C. P. and Craigen M. A. 2013 Bioabsorbable Fixation of Scaphoid Fractures and Non-Unions; Analysis of Early Clinical Outcomes Hand Surg. 18 343-349

CrossrefGoogle Scholar

[6]

Daniels A. U., Chang M. K. O., Andriano K. P. and Heller J. 1990 Mechanical properties of biodegradable polymers and composites proposed for internal fixation of bone J. Appl. Biomater. 1 57-78

CrossrefGoogle Scholar

[7]

Dias J. J. 2001 Definition of Union after Acute Fracture and Surgery for Fracture Nonunion of the Scaphoid 321-325

Google Scholar

[8]

Harrison A. K., Gioe T. J., Simonelli C., Tatman P. J. and Schoeller M. C. 2010 Do porous tantalum implants help preserve bone?: Evaluation of tibial bone density surrounding tantalum tibial implants in TKA Clin. Orthop. Relat. Res. 468 2739-2745

CrossrefGoogle Scholar

[9]

Aworinde A. K., Adeosun S. O., Oyawale F. A., Akinlabi E. T. and Emagbetere E. 2018 Mechanical Strength and Biocompatibility Properties of Materials for Bone Internal Fixation : A Brief Overview Proceedings of the International Conference on Industrial Engineering and Operations Management 1-12

Google Scholar

[10]

Xiao L., Wang B., Yang G. and Gauthier M. 2012 Poly(Lactic Acid)-Based Biomaterials: Synthesis,

Modification and Applications 247-282

Google Scholar

[11]

Li Z. and Wang C. 2013 Effects of Working Parameters on Electrospinning One-Dimensional Nanostructures Electrospinning Technique and Unique Nanofibers 15-28

CrossrefGoogle Scholar

[12]

Adeosun S. O., Aworinde A. K., Diwe I. V. and Olaleye S. A. 2016 Mechanical and Microstructural Characteristics of Rice Husk Reinforced Polylactide Nanocomposite West Indian J. Eng. 39 63-71

Google Scholar

[13]

Wang Z., Wang Y., Ito Y., Zhang P. and Chen X. 2016 A comparative study on the in vivo degradation of poly(L-lactide) based composite implants for bone fracture fixation Sci. Rep. 6 1-12

Google Scholar

[14]

Wang X., Lou T., Zhao W., Song G., Li C. and Cui G. 2015 The effect of fiber size and pore size on cell proliferation and infiltration in PLLA scaffolds on bone tissue engineering J. Biomater. Appl. 30 1545-1551

CrossrefGoogle Scholar

[15]

Song P. et al 2018 Novel 3D porous biocomposite scaffolds fabricated by fused deposition modeling and gas foaming combined technology Compos. Part B Eng. 152 151-159

CrossrefGoogle Scholar

[16]

Duarte A. R. C., Mano J. F. and Reis R. L. 2010 Novel 3D scaffolds of chitosan-PLLA blends for tissue engineering applications: Preparation and characterization J. Supercrit. Fluids 54 282-289

CrossrefGoogle Scholar

[17]

ASTM-D695 2015 D 695-15 Compressive Properties of Rigid Plastics 1 1-8

Google Scholar

[18]

Chen Y. et al 2017 Mechanical properties and biocompatibility of porous titanium scaffolds for bone tissue engineering J. Mech. Behav. Biomed. Mater. 75 169-174 Nov.

CrossrefGoogle Scholar

[19]

Farah S., Anderson D. G. and Langer R. 2016 Physical and mechanical properties of PLA, and their functions in widespread applications — A comprehensive review ☆ 107 367-392

Google Scholar

[20]

Premalal H. G. B., Ismail H. and Baharin A. 2002 Comparison of the mechanical properties of rice husk powder filled polypropylene composites with talc filled polypropylene composites Polym. Test. 21 833-839 Jan.

CrossrefGoogle Scholar

[21]

Pozuelo M. et al 2017 Stretching Micro Metal Particles into Uniformly Dispersed and Sized Nanoparticles in Polymer Sci. Rep. 7 3-7

Google Scholar

[22]

Šupová M., Martynková G. S. and Barabaszová K. 2011 Effect of Nanofillers Dispersion in Polymer Matrices: A Review Sci. Adv. Mater. 3 1-25

CrossrefGoogle Scholar

[23]

Liu J., Gao Y., Cao D., Zhang L. and Guo Z. 2011 Nanoparticle dispersion and aggregation in polymer nanocomposites: Insights from molecular dynamics simulation *Langmuir* 27 7926-7933

[Crossref](#)[Google Scholar](#)

[24]

Esposito Corcione C. et al 2018 Highly loaded hydroxyapatite microsphere / PLA porous scaffolds obtained by fused deposition modelling *Ceram. Int.* 1-8

[Google Scholar](#)

[25]

Esposito Corcione C. et al 2019 Highly loaded hydroxyapatite microsphere / PLA porous scaffolds obtained by fused deposition modelling *Ceram. Int.* 45 2803-2810

[Crossref](#)[Google Scholar](#)

[26]

Correlo V. M., Boesel L. F., Bhattacharya M., Mano J. F., Neves N. M. and Reis R. L. 2005 Properties of melt processed chitosan and aliphatic polyester blends *Mater. Sci. Eng. A* 403 57-68

[Crossref](#)[Google Scholar](#)

[27]

Frans H. 1995 Impact Testing of Polypropylene Blends and Composites *Polym. Eng. Sci.* 35 1962-1971

[Crossref](#)[Google Scholar](#)

[28]

Narayanan G., Vernekar V. N., Kuyinu E. L. and Laurencin C. T. 2016 Poly (lactic acid)-based biomaterials for orthopaedic regenerative engineering *Adv. Drug Deliv. Rev.* 107 247-276

[Crossref](#)[Google Scholar](#)

[29]

Taylor D. 2017 Measuring Fracture Toughness in Biological Materials *J. Mech. Behav. Biomed. Mater.*

Google Scholar

[30]

Orellana J. L., Wichhart D. and Kitchens C. L. 2018 Mechanical and Optical Properties of Polylactic Acid Films Containing Surfactant-Modified Cellulose Nanocrystals J. Nanomater. 2018 1-12 Oct.

CrossrefGoogle Scholar

[31]

Moradkhani A., Baharvandi H., Tajdari M., Latifi H. and Martikainen J. 2013 Determination of fracture toughness using the area of micro-crack tracks left in brittle materials by Vickers indentation test J. Adv. Ceram. 2 87-102

CrossrefGoogle Scholar

[32]

Li W.-L. and Li J. C. M. 1989 The effect of grain size on fracture toughness Philos. Mag. A Phys. Condens. Matter, Struct. Defects Mech. Prop. 59 1245-1261

Google Scholar

[33]

Zakaria Z. et al 2013 Mechanical Properties and Morphological Characterization of PLA/Chitosan/Epoxidized Natural Rubber Composites Adv. Mater. Sci. Eng. 2013 1-7

CrossrefGoogle Scholar

Export references: BibTeX RIS

Abstract

REFERENCES

brightrecruits.com jobs

Windows DevOps Engineer (IT-CDA-AD-2020-68-LD): CERN

CERN

Real-Time Control System Software Engineer (TE-EPC-CCS-2020-66-LD): CERN

CERN

Principal Systems Engineer – Project Engineer: QinetiQ

[Journals](#)[Books](#)[About IOPscience](#)[Contact us](#)[Developing countries access](#)[IOP Publishing open access policy](#)

[IOP Publishing home](#)

© Copyright 2020 IOP Publishing [Terms & conditions](#) [Disclaimer](#) [Privacy & cookie policy](#) This link opens in a new tab. This site uses cookies. By continuing to use this site you agree to our use of cookies.