

**THE RIGHT RESOURCE FOR EVERY
OIL AND GAS PROFESSIONAL**



SPE Nigeria Annual International Conference and Exhibition

August 11–13, 2020

Virtual

[Day 1 Tue, August 11, 2020](#)

ISBN:

978-1-61399-785-7

HOME

LATEST CONFERENCE

ALL YEARS

OTHER PROCEEDINGS

VISIT SPE

CITATION MANAGER

Society of Petroleum Engineers (SPE)

Skip Nav Destination

SPE Nigeria Annual International Conference and Exhibition

August 11–13, 2020

Virtual

Day 1 Tue, August 11, 2020

ISBN: 978-1-61399-785-7

Previous Paper

Next Paper

Numerical Based Optimization for Natural Gas Dehydration and Glycol Regeneration

Emmanuel E. Okoro ; Samuel E. Sanni ; David I. Olatunji ; Paul Igbinedion ; Babalola Oni ; Oyinkepreye D. Orodu

Paper presented at the SPE Nigeria Annual International Conference and Exhibition, Virtual, August 2020.

Paper Number: SPE-203751-MS

<https://doi.org/10.2118/203751-MS>

Published: August 11 2020

Cite

Share Icon

Share

Get Permissions

Abstract

Exergy is a simultaneous measure of the quantity and quality of energy. This helps to identify the inefficiency of the process and allows engineers to determine the cause and magnitude of the loss for each operating unit. Natural gas dehydration via absorption using glycol is the most economically attractive approach, and this advantage can only stand if lower energy consumption relative to adsorption process can be obtained; thus, timely prediction and identification of energy consumption is vital. In this study, an energy utilization predictive model for natural gas dehydration unit energy consumption was developed. This numeric approach will increase accuracy and reduce the high simulation time often encountered in using other simulation software. To achieve this novel idea, a multilayer perceptron approach which is a deep learning neural network model built on python using Tensorflow was adopted. The model used for this study is implemented to further increase the accuracy of the output set variables which are matched with simulation result. Since we are dealing with a non-linear function, rectified linear unit (ReLU) function was used to activate the neurons in hidden layers so as to strengthen the model to be more flexible in finding relationships which are arbitrary in the input parameter. These input parameters are fed into the steady state model and sent to various branches of fully connected neural network models using a linear activation function. Each branch produces a result for each output parameter thereby fitting the model by reducing the mean squared error loss. The training data were not normalized but left in their original form. Results showed that the adopted double hidden layer with 5 branches are uniquely branched in such a way that it predicts values for a single output variable, which is an upgrade to the former work done with a single hidden layer in literature. The accuracy analysis showed that the proposed double hidden layer approach in this study out-performed the single hidden layer.

Keywords:upstream oil & gas, neural network model, artificial intelligence, dehydration system, energy consumption, neural network, midstream oil & gas, input parameter, output variable, gas dehydration unit energy consumption

Subjects:Processing Systems and Design, Information Management and Systems, Dehydration, Neural networks

Copyright 2020, Society of Petroleum Engineers

You do not currently have access to this content.

Sign in

Don't already have an account? Register

Personal Account

Email Alerts

Proceedings Paper Activity Alert Alert

Latest Conference Proceeding Alert

Suggested Reading

Formation of Carbonyl Sulfide during Molecular Sieve Dehydration Process from High Sour Natural Gas in China

10IOGCEC

Hydrocarbon Recovery From Glycol Reboiler Vapor With Glycol- Cooled Condensers

93EPEC

Improving Gas Dehydration Using Pre-Inhibited Glycol

17NAIC

Glycol Used for Natural Gas Dehydration: Evaluation of Subsurface Transport and Fate Issues
99EPEC

Accept
Optimization for Natural Gas Dehydration and Glycol Regeneration

[Emmanuel E. Okoro](#) ;

[Samuel E. Sanni](#) ;

[David I. Olatunji](#) ;

[Paul Igbinedion](#) ;

[Babalola Oni](#) ;

[Oyinkepreye D. Orodu](#)

Paper presented at the SPE Nigeria Annual International Conference and Exhibition, Virtual, August 2020.

Paper Number: SPE-203751-MS

<https://doi.org/10.2118/203751-MS>

Published: August 11 2020

- Cite
- Share Icon **Share**
- **Get Permissions**

Abstract

Exergy is a simultaneous measure of the quantity and quality of energy. This helps to identify the inefficiency of the process and allows engineers to determine the cause and magnitude of the loss for each operating unit. Natural gas dehydration via absorption using glycol is the most economically attractive approach, and this advantage can only stand if lower energy consumption relative to adsorption process can be obtained; thus, timely prediction and identification of energy consumption is vital. In this study, an energy utilization predictive model for natural gas dehydration unit energy consumption was developed. This numeric approach will increase accuracy and reduce the high simulation time often encountered in using other simulation software. To achieve this novel idea, a multilayer perceptron approach which is a deep learning neural network model built on python using Tensorflow was adopted. The model used for this study is implemented to further increase the accuracy of the output set variables which are matched with simulation result. Since we are dealing with a non-linear function, rectified linear unit (ReLU) function was used to activate the neurons in hidden layers so as to strengthen the model to be more flexible in finding relationships which are arbitrary in the input parameter. These input parameters are fed into the steady state model and sent to various branches of fully connected neural network models using a linear activation function. Each branch produces a result for each output parameter thereby fitting the model by reducing the mean squared error loss. The training data were not normalized but left in their original form. Results showed that the adopted double hidden layer with 5 branches are uniquely branched in such a way that it predicts values for a single output variable, which is an upgrade to the former work done with a single hidden layer in literature. The accuracy analysis showed that the proposed double hidden layer approach in this study out-performed the single hidden layer.

Keywords:

[upstream oil & gas](#), [neural network model](#), [artificial intelligence](#), [dehydration system](#), [energy consumption](#), [neural network](#), [midstream oil & gas](#), [input parameter](#), [output variable](#), [gas dehydration unit energy consumption](#)

Subjects:

[Processing Systems and Design](#), [Information Management and Systems](#), [Dehydration](#), [Neural networks](#)

Copyright 2020, Society of Petroleum Engineers
You do not currently have access to this content.

Pay-Per-View Access

\$28.00

BUY THIS ARTICLE

Annual Article Package – 25

\$200

BUY DOWNLOADS

Annual Article Package – 50

\$300

BUY DOWNLOADS