

**RESERVOIR CHARACTERIZATION, MODELLING AND LATERAL  
PREDICTIONS USING MULTIVARIATE ANALYSIS: A CASE STUDY OF  
HEMS FIELD, BOHAI BAY, LIAOHE FIELD, CHINA**

**BY**

**ROTIMI, OLUWATOSIN JOHN**

**B. Sc (Geology) Ilorin; M. Sc (Applied Geophysics) Ibadan**

**A THESIS SUBMITTED**

**TO**

**THE DEPARTMENT OF PETROLEUM ENGINEERING, SCHOOL OF  
ENGINEERING AND TECHNOLOGY, COLLEGE OF SCIENCE &  
TECHNOLOGY, COVENANT UNIVERSITY, OTA**

**IN PARTIAL FULFILMENT OF THE REQUIREMENTS FOR THE AWARD OF  
DOCTOR OF PHILOSOPHY (Ph.D) DEGREE IN PETROLEUM GEOPHYSICS**

**JULY, 2013**

## CERTIFICATION

We certify that the thesis titled “Reservoir Characterization, Modelling and Lateral Predictions Using Multivariate Analysis: A Case Study of Hems field, Bohai bay, Liaohe field, China.” is an original work carried out by Mr. Rotimi Oluwatosin John (CUGP070197) in the Department of Petroleum Engineering, Covenant University, Ota, under the supervision of Prof. B. D. Ako and Dr. C. C. Uhuegbu. We have examined and found the work acceptable for the award of a degree of Doctor of Philosophy in Petroleum Geophysics.

Prof. B. D. Ako  
Department of Applied Geophysics,  
Federal University of Technology, Akure

Signature / Date .....

Dr. C. C. Uhuegbu  
Department of Physics,  
Covenant University

Signature / Date .....

Dr. O.D. Orodu  
Head, Department of Petroleum Engineering,  
Covenant University

Signature / Date .....

Prof. A. I. Olayinka  
(External Examiner)  
Department of Geology,  
University of Ibadan

Signature / Date.....

Prof. S.S. Adefila  
Dean, College of Science & Technology  
Covenant University

Signature / Date.....

## **DEDICATION**

This research work is dedicated to my Lord Jesus Christ, the wisdom and source of life.

May His name be praised forever for his continual release of grace and mercies in divine revelations to conclude this study. I also dedicate this to my lovely family, especially to my adorable daughter - Delightful-Laughter for being the latest *Abidemi*.

## ACKNOWLEDGEMENTS

To the owner of the universe, the almighty God who gave me all I needed – wisdom, sound health, grace, mercy and life to accomplish this task with outstanding success, to him I ascribe all praise. He alone is worthy.

I will like to appreciate my supervisor Prof. B. D. Ako, for his mentorship, immense contribution, interest, advice, correction and thorough scrutiny of this work, your efforts have added glamour to this work this much sir. I also want to thank Dr. C.C. Uhuegbu for accepting to co-supervise me when he least expected after the demise of Prof. E. B. Babatunde. I like to appreciate Prof. C. T. Ako for his continuous fatherly advice towards the completion of this work. The support of the Head of the Department of Petroleum Engineering – Dr. O. D. Orodu is well appreciated. I am also grateful for the support and assistance of my colleagues (academic and non-academic) in the Department.

I want to appreciate the Chancellor of Covenant University for the vision that birthed this great Institution. I also appreciate the Management of Covenant University for giving me the enabling environment to perform and excel. I am indebted to TWAS-CAS for granting me the postgraduate fellowship to undertake the research work. I like to appreciate the Management of the Institute of Geology and Geophysics, CAS, Beijing, China for giving me a congenial atmosphere to study and research. I thank the following persons for their roles in the completion of this work: Prof. Mme Fu, CAS head office, Beijing, Prof. T. Zhou, IGGCAS. This will be incomplete without mentioning and appreciating my co-supervisor in the Key laboratory of Petroleum Resources, IGGCAS - Prof. Wang Zhenli, thank you sir for creating space for me in your laboratory and to be

part of your research team. Special appreciation goes to the China National Oil Corporation (CNOOC) for the release of data for this study.

Many thanks to the following persons; Shu Mengcheng, Liang Yao, Zhou, Xue, Dianbo Dai, Anna, Ella, Hyacinth Nnamchi, Ugochukwu Okoro, Dr. Adeoye Emmanuel, Martins Omorogie, Peter Okoli, Emeka Enebeli, Quentin of Sinopec in Beijing, Mrs Elozino Olaniyan of SNEPCO, the member of the worship team Haidian English fellowship, Beijing, Carol, Lesley, John, and Bode Matthew of Sahara Energy. A warm thanks to Dr. Abiodun Adebayo for assistance and encouragement all the way.

To Pastor (Dr.) Daniel Rotimi, thanks for being an encourager and a mentor, your family is blessed as always. This will be incomplete without thanking the family of Barr. Rotimi Jacobs (SAN) for being used of God to start this in 2004, your family is blessed and your generation will always experience help from God. To my siblings, Sister Mayowa, Dr. Muyiwa, Kayode, Fikemi, Bukola, Wisdom, IseOluwa, Cousins, nephews and nieces, you are dear to my heart and I appreciate your love.

To my amiable and wonderful family, I am grateful for your understanding and support all these years, my darling wife, Omolola - you are a jewel indeed and will surely enjoy Gods' favour on all sides. My beautiful children, David Titoluwalase and Gabriella Delightful-Laughter, you are ever loved and will surely surpass this in your own time.

Daddy loves you as always!

Daddy and Mummy, once again, I am most fortunate and grateful to God for blessing me with such wonderful parents. I am very grateful for all you have done. May you live long to reap the fruits of your labour, amen.

## LIST OF ABBREVIATIONS

AI	Acoustic Impedance
SP	Spontaneous Potential
LLD	Deep Laterolog
EI	Elastic Impedance (EI 10, 20, 30)
$V_p$	P wave-velocity
$V_s$	S wave-velocity
$V_p/V_s$	P-velocity/ S-velocity Ratio
$\phi$	Porosity (PHI)
CAL	Caliper log
AC	Acoustic/Sonic log
GR	Gamma Ray
$S_w, S_{hc}$	Water Saturation, Hydrocarbon Saturation
Temp	Temperature Log
BVW	Bulk Volume Water
CNL	Compensated Neutron Log
$R_w$	Water Resistivity
TST	True Stratigraphic Thickness
TVT	True Vertical Thickness
N/G	Net to Gross
K	Permeability
Electrofacies	L_facies
$\rho$	Rho (DENSITY)

$\mu$	Mu
$\lambda$	Lambda
$\mu\rho$	Mu Rho
$\lambda\rho$	Lambda Rho
SMT	Seismic MicroTech Software (The Kingdom Suite)
IP	Interactive Petrophysics Software
HRS	Hampson Russell Suite (CGG Veritas)
SIS	Sequential Indicator Simulation
TGS	Truncated Gaussian Simulation
SGS	Sequential Gaussian Simulation
ROI	Region of Interest
RMS	Root Mean Square

### **Measurement and property Symbols**

cm	Centimetre
m	Metre
$^{\circ}\text{C}$	Degree Celsius
g	Gramme
ms/gcc	Milliseconds per Gramme per Cubic Centimetre
$\mu$	Shear Modulus
$\kappa$	Bulk Modulus
$\sigma$	Poisson Ratio

## TABLE OF CONTENTS

TITLE PAGE.....	i
CERTIFICATION.....	ii
DEDICATION.....	iii
ACKNOWLEDGEMENTS.....	iv
LIST OF ACRONYMS AND ABBREVIATIONS.....	vi
LIST OF FIGURES.....	xii
LIST OF TABLES.....	xxv
ABSTRACT.....	xxvi

### CHAPTER ONE

#### INTRODUCTION

1.1 Overview of study.....	1
1.2 Basic Theory of data set.....	8
1.2.1 Well logs.....	9
1.2.2 Seismic data.....	10
1.3 Statement of the Problem.....	14
1.4 Aim and Objectives of Study.....	15
1.5 Methodology.....	16

### CHAPTER TWO

#### LITERATURE REVIEW

2.1 Previous work done using well logs and seismic data for reservoir characterization.....	17
--	----



2.2	Location of study area.....	21
2.2.1	Geology of study area.....	21
2.3	Stratigraphic sequence.....	26

## **CHAPTER THREE**

### **MATERIALS AND METHODS**

3.1	Location and data.....	30
3.2	Well logs workflow.....	30
3.3	Well logs normalization.....	33
3.4	Clustering analysis.....	39
3.5	Missing logs prediction and computation.....	51
3.6	Well logs upscaling.....	53
3.7	Variogram analysis and simulation algorithms.....	56
3.8	Seismic inversion and volume prediction.....	62
3.8.1	Seismic inversion.....	62
3.8.2	Multi-attribute volume prediction.....	68
3.9	Geomodel - 3D Grid model.....	73
3.10	Formulae for the logs rock properties.....	73
3.11	Seismic stratigraphy analysis methods.....	76

## **CHAPTER FOUR**

### **RESULTS AND DISCUSSION**

4.1	Surfaces and Zones.....	80
-----	-------------------------	----

4.2	Stratigraphical patterns.....	80
4.3	Structural pattern.....	83
4.4	Well logs analysis and interpretations.....	93
4.4.1	Correlation.....	93
4.5	Facies model results.....	103
4.5.1	Surfaces.....	103
4.5.2	Facies log.....	103
4.5.3	Grid cell size.....	105
4.5.4	Zone partitions and Vertical boundaries.....	105
4.6	Algorithm/variogram.....	108
4.6.1	Quality control check of picked surfaces.....	111
4.7	Reservoir properties model results.....	111
4.8	Uncertainty analysis.....	111
4.9	Facies model discussion.....	114
4.10	Geologic model (Geomodel).....	119
4.11	Validation of the facies model.....	119
4.12	Facies constrained structural styles and rock properties.....	123
4.12.1	Structural styles and features analysis.....	123
4.13	Stratigraphical analysis.....	128
4.13.1	Seismic stratigraphy and facies.....	128
4.14	Porosity and permeability model discussion.....	138
4.15	Application of seismic attributes for characterization.....	146
4.16	Acoustic Impedance modeling discussion.....	146

4.17	Relationship definitions.....	156
4.18	Offset correlation.....	173
4.19	Zone property maps.....	183
4.20	Prediction beyond well control .....	186
4.21	Sources of error.....	192

## **CHAPTER FIVE**

### **CONCLUSIONS AND RECOMMENDATIONS**

5.1	Conclusion.....	193
5.2	Recommendations.....	195

<b>REFERENCES.....</b>	<b>198</b>
------------------------	------------

## LIST OF FIGURES

<b>Figure 1.1:</b> Simple raypath diagram showing relationships between incidence, reflected and transmitted wave	12
<b>Figure 2.1:</b> Base-map of Hems field showing wells, inlines and crosslines	22
<b>Figure 2.2:</b> Location of the Bohai Basin	24
<b>Figure 2.3:</b> Distribution of Sags, Uplifts and main oil and gas fields in the distal portion of Bohai Bay	25
<b>Figure 2.4:</b> Stratigraphic column in part Bohai Bay Basin	27
<b>Figure 3.1:</b> Methodology chart for integrated reservoir characterization and modeling	31
<b>Figure 3.2:</b> Schematic presentation of Normalization parameters for the same curves (gamma ray). <i>A</i> is appearance before normalization, <i>B</i> is appearance after normalization	35
<b>Figure 3.3:</b> Normalization procedure (2 point) used for SP log	37
<b>Figure 3.4:</b> Histograms used for normalization showing full log in <i>A</i> and upper and lower zones in <i>B</i> and <i>C</i>	37
<b>Figure 3.5:</b> A normalization result panel showing the lower adjusted portion and respective histograms for upper and lower zones	37
<b>Figure 3.6:</b> Base map of Hems field with available wells and correlation line, inlines and crosslines	38
<b>Figure 3.7:</b> Clustering panel from Interactive Petrophysics™ software (IP) <i>VSH-volume of shale, PHI-porosity, SP-Spontaneous Potential</i>	38
<b>Figure 3.8:</b> All populated cells in clustering run from IP software showing SP-Spontaneous potential, AC-Sonic and Rho-Density logs	41
<b>Figure 3.9:</b> All populated cells in clustering run from IP software showing VSH-volume of shale, PHI-porosity and SP-Spontaneous Potential logs	41
<b>Figure 3.10:</b> Cluster grouping dendrogram for cluster group 5	42
<b>Figure 3.11:</b> Cluster grouping dendrogram for cluster group 8	42
<b>Figure 3.12:</b> Cluster grouping dendrogram for cluster group 11	43
<b>Figure 3.13:</b> Cluster grouping dendrogram for cluster group 13	43

<b>Figure 3.14:</b> Cluster grouping dendrogram for cluster group 3	44
<b>Figure 3.15:</b> Cluster operational panel showing histograms and crossplots on model using 7wells and forming 11 groups	44
<b>Figure 3.16:</b> Cluster operational panel showing histograms and crossplots on model using 8 wells and forming 15groups	45
<b>Figure 3.17:</b> Facies clustering model for all groups showing curve names, initial 15 seed clusters and all experimented clusters	47
<b>Figure 3.18:</b> Crossplots and histogram panels for clustering group 5	47
<b>Figure 3.19:</b> Crossplots and histogram panels for clustering group 3	48
<b>Figure 3.20:</b> Randomness plot for the groups in the clustering run for electrofacies	48
<b>Figure 3.21:</b> Multi well correlation panel of line 8 wells used in model building showing the result of the clustering run for all groups	49
<b>Figure 3.22:</b> Result of the unsupervised neural network that classified the acoustic impedance values from the inversion result into 2 classes	50
<b>Figure 3.23:</b> Histogram panel for predicted logs showing distribution within Gaussian fit	52
<b>Figure 3.24:</b> Variation of Bin distributions for predicted logs	52
<b>Figure 3.25:</b> Raw porosity logs from wells in the study area	55
<b>Figure 3.26:</b> Upscaled porosity logs in a simulation case for further analysis	55
<b>Figure 3.27:</b> Petrel data analysis panel showing different fields to be filled for proper anisotropic analysis of data. ( <i>Major direction</i> )	58
<b>Figure 3.28:</b> Petrel data analysis panel showing different fields to be filled for proper anisotropic analysis of data. ( <i>Minor direction</i> )	59
<b>Figure 3.29:</b> Petrel data analysis panel showing different fields to be filled for proper anisotropic analysis of data. ( <i>Vertical direction</i> )	60
<b>Figure 3.30:</b> Closer view the search cone and variogram function panel in Petrel data analysis in the major direction	61
<b>Figure 3.31:</b> Closer view the search cone and variogram function panel in Petrel data analysis in the minor direction	61
<b>Figure 3.32:</b> Closer view the search cone and variogram function panel in Petrel data analysis in the vertical direction	61

<b>Figure 3.33:</b> Composite trace extraction panel by neighbourhood method	63
<b>Figure 3.34:</b> Statistical wavelet extracted for well 43 in the time domain	63
<b>Figure 3.35:</b> Statistical wavelet extracted for well 7 in the time domain	64
<b>Figure 3.36:</b> Statistical wavelet extracted for well 20 on the frequency domain	64
<b>Figure 3.37:</b> Panel showing stretch and squeeze applied to well m77 and correlation parameters	65
<b>Figure 3.38:</b> Panel showing correlation validation after stretch and squeeze operations	65
<b>Figure 3.39:</b> Root mean square (RMS) error plot between original log and inverted result	67
<b>Figure 3.40:</b> Single attribute correlation result panel	69
<b>Figure 3.41:</b> Multi-attribute correlation result panel	69
<b>Figure 3.42:</b> Multi-attribute regression cross-correlation plot for 3 attributes	70
<b>Figure 3.43:</b> Wells – attribute regression correlation for 3 attributes	70
<b>Figure 3.44:</b> Wells – attribute regression correlation for 4 attributes	71
<b>Figure 3.45:</b> Wells – attribute probabilistic neural network correlation for 4 attributes	71
<b>Figure 3.46:</b> Multi-attribute probabilistic neural network cross-correlation plot for Figure 3.41	72
<b>Figure 3.47:</b> Average error plot for wells used in multi-attributes volume prediction	72
<b>Figure 3.48:</b> Log panel for well m34 showing various computed logs.	75
<b>Figure 3.49:</b> Different types of geological boundaries defining seismic sequences	77
<b>Figure 3.50:</b> Divers internal bedforms that typifies different seismic facies within sedimentary sequences identified on seismic section	77
<b>Figure 3.51:</b> Classification of internal reflection patterns of seismic data	78
<b>Figure 3.52:</b> Facies reflection patterns visually identified from seismic data (crossline 1390)	79
<b>Figure 4.1:</b> Seismic volume and horizons interpreted on the study area. Inline 2310 and crossline 1080 is shown on A and C	81
<b>Figure 4.2:</b> Horizons interpreted from the Hems field and presented in table 1	82
<b>Figure 4.3:</b> Thick wedge deposit observed on inline 2186 in the study area	84

<b>Figure 4.4:</b> Regional structural pattern of Liaohe oilfield and buried hill. Seismic section is inline 2186 shown on A	85
<b>Figure 4.5:</b> Regional structural pattern of Liaohe oilfield showing major strike-slip faults. <b>A</b> and <b>B</b> are results of geometric attribute enhanced structural attitude of Hems field. Location of Hems field captured in red oval	87
<b>Figure 4.6:</b> Normal vintage seismic showing inline 2125 prior to structural smoothing	89
<b>Figure 4.7:</b> Inline 2125 after subjecting to structural smoothing with Gaussian filter and edge enhanced operation	89
<b>Figure 4.8:</b> Trace amplitude constrained Quadrature trace on line 2130 with a time slice and fault planes interpreted	90
<b>Figure 4.9:</b> Seismic section showing mapped horizons (Givens, Hallux, Miller and Brisk)	91
<b>Figure 4.10:</b> Variance cube on volume amplitude data to enhance edge effect showing time slice and line 2070	92
<b>Figure 4.11:</b> PCA constrained to local structural dip showing time slice and line 2070	92
<b>Figure 4.12:</b> Field base map with 12 wells shown in figures 4.10 – 4.16	94
<b>Figure 4.13:</b> Various logs interpreted for wells m34 and m36	95
<b>Figure 4.14:</b> Various logs interpreted for wells m47 and m52	97
<b>Figure 4.15:</b> Various logs interpreted for wells m77 and m255	98
<b>Figure 4.16:</b> Various logs interpreted for wells m256 and m531	99
<b>Figure 4.17:</b> Various logs interpreted for wells x7 and x43	100
<b>Figure 4.18:</b> Various logs interpreted for wells x109 and x428	101
<b>Figure 4.19:</b> Correlation line panel with 8wells, 4 logs each and well top delineating hydrocarbon zones interpreted	102
<b>Figure 4.20:</b> Surfaces built from horizon interpretation of the study area. The simulation case and zone inherits its attitude from it	104
<b>Figure 4.21:</b> Inline 2080 and the simulation case for the middle portion on depth property	106

<b>Figure 4.22:</b> Modelled middle portion of the Hems field with bounding horizon Hallux and Miller. Statistics: Top horizon – Hallux, Base horizon – Miller, Number of faults – 16, Number of 3D nodes – 23339403, Number of layers – 400	107
<b>Figure 4.23:</b> 35 of 50 realizations of SIS facies model associations for Hems field	109
<b>Figure 4.24:</b> Mean of 50 realizations of facies model for Hems field	110
<b>Figure 4.25:</b> Intersection fence for facies associations in offset of m34 and m47	113
<b>Figure 4.26:</b> Intersection fence for porosity property in offset of m34 and m47	113
<b>Figure 4.27:</b> Partitioned facies model	115
<b>Figure 4.28:</b> Non-partitioned facies model	115
<b>Figure 4.29:</b> Correlation lines from mean of SIS facies model, lines 1-6	116
<b>Figure 4.30:</b> Correlation lines from mean of SIS facies model, lines 7-11	117
<b>Figure 4.31:</b> All correlation lines intersection and surface locations on SIS facies model	118
<b>Figure 4.32:</b> SIS facies model filtered visualization in direct and inverse cell units	118
<b>Figure 4.33:</b> Lenses of sand and shale facies traced from well m34 captured in red dotted ovals	120
<b>Figure 4.34:</b> Facies models (a.) validation model and (b.) original model	122
<b>Figure 4.35:</b> Lithofacies interpretation result from correlation line (a.) validation model, (b.) original model	122
<b>Figure 4.36:</b> Intersection surface projection of facies model showing hanging and footwall of reverse fault in the east-west direction	124
<b>Figure 4.37:</b> Intersection surface projection of facies model showing hanging and footwall of reverse fault in the east-west direction	124
<b>Figure 4.38:</b> Intersection surface projection of facies model in the east-west direction showing reverse fault blocks	125
<b>Figure 4.39:</b> Intersection surface projection of facies model in the east-west direction showing appearance and disappearance of fault planes	125
<b>Figure 4.40:</b> Intersection surface projection of facies model in the east-west direction showing isolated upthrown (horst) and downthrown fault blocks (graben)	126



<b>Figure 4.41:</b> Intersection surface projection of facies model in the east-west direction showing extended unfaulted surface but still faulted at the base	126
<b>Figure 4.42:</b> Intersection surface projection of facies model showing hanging walls and footwalls of reverse fault in the east-west direction	129
<b>Figure 4.43:</b> Intersection surface projection of anisotropic porosity model for zone showing values across fault blocks in the east-west direction and the variation within the modeled zone	129
<b>Figure 4.44:</b> Intersection surface projection of anisotropic permeability model for zone showing values variation across fault blocks in the east-west direction. Range between 0.35 and 3mD	130
<b>Figure 4.45:</b> Intersection surface projection of hydrocarbon saturation ( $S_{hc}$ ) model for zone showing values across fault blocks in the east-west direction and variation within modeled zone	130
<b>Figure 4.46:</b> Intersection surface projection of Volume of shale ( $V_{sh}$ ) model for zone showing its values across fault blocks in the east-west direction and variation within the modeled zone	131
<b>Figure 4.47:</b> Intersection surface projection of Acoustic impedance (AI) model of zone showing rock property across fault blocks in the east-west direction and variation within the modeled zone	131
<b>Figure 4.48:</b> Crossline 1360 showing the parallel and conformable upper reflections on the field	133
<b>Figure 4.49:</b> Seismic stratigraphic volume attribute showing Chaos attribute for the vintage seismic volume	134
<b>Figure 4.50:</b> Crossline 1390 showing a broader view of the stratigraphy as interpreted from the reflection patterns in the study area	135
<b>Figure 4.51:</b> Crossline 1390 showing a broader view of the stratigraphy and sequence definitions as interpreted from the reflection patterns in the study area	137
<b>Figure 4.52:</b> Porosity volume prediction result from P-impedance inversion	139
<b>Figure 4.53:</b> 35 of 50 realizations of SIS property porosity model for Hems field	140

<b>Figure 4.54:</b> Porosity modeled with co-kriging using secondary property of Permeability (local varying mean)	141
<b>Figure 4.55:</b> Porosity modeled with collocated co-kriging using secondary property of permeability (constant correlation coefficient 0.7676)	141
<b>Figure 4.56:</b> Modeled porosity volume for middle of Hems field using vertical function (i.e. regression based linear correlation cross plot of porosity and permeability)	142
<b>Figure 4.57:</b> Porosity and permeability vertical property crossplot used in the Figure 4.48 model simulation	142
<b>Figure 4.58:</b> Facies constrained SGS porosity model (i.e. facies as secondary variable)	144
<b>Figure 4.59:</b> SIS modeled facies used as secondary property for the porosity model in Figure 4.57	144
<b>Figure 4.60:</b> Initial porosity model intersection view for line 8	145
<b>Figure 4.61:</b> Initial SP model intersection view for line 8	145
<b>Figure 4.62:</b> Facies model from using cutoffs. <i>SP-105</i> and <i>porosity-0.1</i> for line 8	145
<b>Figure 4.63:</b> Acoustic impedance inversion result from STRATA®	148
<b>Figure 4.64:</b> SGS modeled Acoustic impedance property for the middle zone	148
<b>Figure 4.65:</b> Comparison of acoustic impedance inversion output and well logs analysis for XL1355 and well m34	149
<b>Figure 4.66:</b> Comparison of acoustic impedance inversion output and well logs analysis for XL1351 and well m47	150
<b>Figure 4.67:</b> Acoustic impedance and Net to Gross	151
<b>Figure 4.68:</b> Acoustic impedance multiple histogram and cumulative distribution function	151
<b>Figure 4.69:</b> Acoustic impedance property model used for Net to Gross	153
<b>Figure 4.70:</b> Net to gross property derived from Acoustic impedance property using 8000m/s/gcc	153
<b>Figure 4.71:</b> Index filtered Acoustic impedance property model used for Net to gross	154
<b>Figure 4.72:</b> Index filtered Net to gross property derived from Acoustic	

impedance property using 8000m/s/gcc cutoff value	154
<b>Figure 4.73:</b> Index filtered SGS modeled Elastic impedance 10 (EI10)	155
<b>Figure 4.74:</b> Index filtered SGS modeled Elastic impedance 20 (EI20)	155
<b>Figure 4.75:</b> Surface maps of the three regions of interest horizon blocks chosen for relation definitions. (1) Seismic RMS amplitude of the ROI horizon surfaces, (2) hydrocarbon saturation property of the ROI horizon surfaces	157
<b>Figure 4.76:</b> Regions of interest (ROI) RMS amplitude volumes within the larger survey for the field of study showing the encapsulated wells	157
<b>Figure 4.77:</b> Regions of interest (ROI) porosity modelled property (middle portion of volume) sampled into seismic resolution within the larger survey for the field of study	158
<b>Figure 4.78:</b> Sculptured horizon cubes of Regions of interest (ROI) for porosity modelled property and RMS amplitude	158
<b>Figure 4.79:</b> Enlarged view of ROI horizon cube A, showing wells and depth values. The attitude of the horizon and zone is clearly seen here	159
<b>Figure 4.80:</b> Enlarged view of the ROI horizon cube B, showing wells and depth values. The attitude of the horizon and zone is clearly seen here	160
<b>Figure 4.81:</b> Enlarged view of the ROI horizon cube C, showing wells and depth values. The attitude of the horizon and zone is clearly seen here	161
<b>Figure 4.82:</b> Rock property surface attribute extraction for horizon cube A at 90 m below surface	164
<b>Figure 4.83:</b> Rock property surface attribute extraction for horizon cube A at 90 m below surface	165
<b>Figure 4.84:</b> Rock property surface attribute extraction for horizon cube B at 120 m below surface	166
<b>Figure 4.85:</b> Rock property surface attribute extraction for horizon cube B at 120 m below surface	167
<b>Figure 4.86:</b> Rock property surface attribute extraction for horizon cube C at 105 m below surface	168
<b>Figure 4.87:</b> Rock property surface attribute extraction for horizon cube C	

at 105 m below surface	169
<b>Figure 4.88:</b> Well logs section and an intersection slice with facies model projection for wells within horizon cube A	174
<b>Figure 4.89:</b> Well logs section and an intersection slice with facies model projection for wells within horizon cube B	175
<b>Figure 4.90:</b> Well logs section and an intersection slice with facies model projection for wells m34 and m47 within horizon cube B	176
<b>Figure 4.91:</b> Well logs section and an intersection slice with facies model projection for wells m47 and m36 within horizon cube B	177
<b>Figure 4.92:</b> Combination of all wells in horizon block B and displayed in Figures 4.88, 4.89 and 4.90	178
<b>Figure 4.93:</b> Well logs section and an intersection slice with facies model projection for wells m47 and m69 within horizon cube C	179
<b>Figure 4.94:</b> Well logs section and an intersection slice with facies model projection for wells m69 and m255 within horizon cube C	180
<b>Figure 4.95:</b> Well logs section and an intersection slice with facies model projection for wells within horizon cube C	181
<b>Figure 4.96:</b> Combination of all wells in horizon block C and displayed in Figures 4.92, 4.93 and 4.94.	182
<b>Figure 4.97:</b> Average porosity map for modeled zone	184
<b>Figure 4.98:</b> Average permeability map for modeled zone	184
<b>Figure 4.99:</b> Average hydrocarbon saturation map for modeled zone	185
<b>Figure 4.100:</b> Average volume of shale map for modeled zone	185
<b>Figure 4.101:</b> Average Acoustic impedance (AI) map for modeled zone	187
<b>Figure 4.102:</b> Isopach map for sand facie in modeled	187
<b>Figure 4.103:</b> Basemap of study area showing locations outside well control	189
<b>Figure 4.104:</b> Intersection view of wedge structure from B part of Figure 4.102 showing Inline 2097 and wells	190
<b>Figure 4.105:</b> Intersection view of wedge structure from B part of Figure 4.102 showing continuity on Inline 2097 and wells	190
<b>Figure 4.106:</b> Intersection blocks from B part of figure 4.102	191

## LIST OF TABLES

<b>Table 3.1:</b> Types and descriptions of well logs	32
<b>Table 4.1:</b> Horizons interpreted defining the different hydrocarbon zones in the study area	82

Rotimi O.J., 2013

## ABSTRACT

Qualitative and quantitative predictions of reservoir properties and geometries beyond well control are vital to understanding the intrinsic characteristics of subsurface formations. Using well log data, 3D Seismic data, Geostatistical simulations, reservoir characterization, modeling via multivariate analysis was carried out for and lateral predictions on data set obtained from Liaohe field, western sag, Bohai Bay, Northern China. This sag is an intra-cratonic basin of Archean to Recent age.

Stratigraphic analysis, structural analysis, geomodel building and geostatistical methods were used. Well logs methods include conventional interpretation by picking sand units based on Self potential log (SP) and Resistivity logs (LLD) in addition to computation of volume of shale and other petrophysical properties. Unavailable logs like Density and Neutron were predicted from a cored well whilst missing logs sections were predicted using neural networks and fuzzy logic. Clustering technique was employed to predict facies (electrofacies) occurrences based on various log types. Sand tops earlier picked from well logs were laterally traced on seismic sections after well to seismic tie. Structural interpretation was done to map the architectural pattern of the rock units. The post-stack seismic inversion was done and calibrated with logs from 12 wells producing acoustic impedance and elastic impedance volumes. Multi-attribute analysis was used to predict rock properties like porosity from inversion results and vintage seismic data. Modeling of variogram and structural elements was done, after which suitable geostatistical simulation algorithms were used to populate cells and realize multiple equiprobable rock properties for the zone of interest after upscaling all needed rock properties into the earlier built non-partitioned simulation case. These were achieved using standard software such as Petrel<sup>®</sup>2008, CGGVeritas<sup>™</sup> Hampson Russell suite (2008), Interactive Petrophysics v3.5, Kingdom Suite (SMT) 2008, GeoGraphix<sup>®</sup> 2008 and Surfer 9 (Golden Software).

Results show that clustering models converged to 2 classes namely sand and shale. Sand and shale sequences are fairly mixed and vertically inconsistent as a result of rapid deposition amidst unconsolidation on the toe of the sag structure. Petrophysical values viz hydrocarbon saturation is above 70%, porosity between 0.1 and 0.4, permeability between 0.6 and 3.0mD and volume of shale between 0.3 and 0.8. Structurally, 35 major and minor faults were mapped with 15 used for modeling. Prevailing fault orientation is northeast/southwest, dipping south-easterly and trending northwest-southeast direction. Bedforms are complex with gradual lateral changes in lithofacies. Sharp boundaries in horizontal direction define different depositional facies with a flexible non-partitioned model adopted. The lithofacies model result showed continuous lithological units with inconsistencies of stratigraphic and structural truncations which were also replicated on the rock properties model with clear heterogeneity seen in the observed values. Horizon cubes produced in regions of interest defined relationships that are clearly correlative with rock properties than with seismic attributes/properties. Majority, some of the properties predicted from multiattribute analysis of seismic data calibrated with computed logs correlated well with the simulated rock property volumes.

In conclusion, successful prediction has been done for rock properties at inter-well points and locations beyond well control. The heavy hydrocarbon in reservoir units of the field can be recovered by steam injection method (SAGD). The methodology and interpretation approach adopted in this work can be implemented initially with very few wells for multiattribute volume prediction, seismic inversion and on a larger scale with more wells for geostatistical simulations and modeling.